

# Almit Flux Agents (perfect wettability, easy in use)

Flux for production and rework. Excellent force, easy handling.

## Almit-Flux Agents

The perfectly matched supplements for production and repair purposes.

All Almit flux agents properties correspond with all other Almit products, the composition of which eliminates crystallisation. This is one of the preconditions that need to met for applications in the aerospace industry including NASA-Space Shuttle.



### BM-1 RMA

Fluxgel "no clean", ideally suited for BGA- and Flip Chip assembly and rework.

Can be applied by means of stencil plate or dispenser, automatically or manually.

Available in 5cc, 10cc, 30cc cartridge and 50g Jar.



#### ■ Properties

Solid content:	60,0%
Relative density:	1,081
Classification :	L1



Pict.: Dispenser cartridge

### BM-5000 RMA

Flux "no clean", ideally for BGA- repair and reworking.

Can be applied with flux pen or brush.

Available in 15ml bottle with brush cap, 250ml, 1000ml bottle, 5000ml container and refillable flux pens.



#### ■ Properties

Solid content:	27,0%
Relative density:	0,925
Classification:	L1



Pict.: Pentelpen



Pict.: Boncote ESD safe

### RC-15SH RMA

Flux "no clean", ideally for repair and reworking.

Can be applied with flux pen or brush.

Available in 15ml bottle with brush cap, 250ml, 1000ml bottle, 5000ml container and flux pen.

Also available with less solid content for wave soldering applications. Bigger containers available on request.



#### ■ Properties

Solid content:	12,0%
Relative density:	0,821
Classification:	L1



Pict.: Flux pen

### RC-281PF

Flux, highly reliability and desirable countermeasurements against bridges and icicles.

Can be applied with a brush.

Available in 15ml bottle with brush cap, 250ml, 1000ml bottle and 5000ml container.

Bigger containers available on request.



#### ■ Classification

Solid content:	12,0%
Relative density:	0,815
Classification:	M1



Pict.: 15ml bottle with brush cap